



Technical Data Sheet

Exterior Stain Gold

Product code: E/70XX

Color: Available in 13 Natural colors

Composition and Application Field

Exterior Gold Stain is a range of concentrated dyes and stainers dispersed in siutable solvent (turpentine) to emphasize their colouristics effect. Exterior Gold Stain comes in many different colors to choose form, and they are fully transparent and display the details of woods. These stains are used most exclusively on all types of wood, plywood and solid woods. They are designed to use for outdoor furnitures.

Available colors

| E/7001 | Douglas | E/7011 | Black |
|--------|-----------|--------|----------------|
| E/7002 | Pine | E/7012 | Dark Oak |
| E/7003 | Light Oak | E/7013 | Medium Oak |
| E/7004 | Chestnut | E/7014 | Walnut Antique |
| E/7005 | Cherry | E/7015 | Walnut |
| | | | |

E/7003 Crierry E/7013 Walnut
E/7006 Yellow Mahogany E/7016 Walnut Sucro
E/7007 Red Mahogany E/7017 Light Green
E/7008 Mahogany E/7018 Dark Green
E/7009 Brown E/7019 White

E/7010 Dark Brown

Product Preperation Dilution

After mixing the product, it's preferable to dilute with turpentine. The dilution is related to the concentration required of the color on the wood. The dilution varies from 200% to 500%.

NB: It is not suggested to mix this product with NC or PU product, but it is posible to use it with alkyd system specially with our luce solvent base system.

Technical Characteristics

Physical Properties

| Specific gravity (according to the color) | 0.87 | (± 0,025) Kg/I |
|---|------|----------------|
| * Viscosity.Ford | 10 | (± 1) Sec. |
| 4/25°C | | |
| Weight solids | 24% | (± 1) Kg/Kg |
| Flash Point | 21 | grades |
| | | centigrade |

(Abel Pensky closed cup)

N.B: The coverage depends on the absorption of the subtract and the percentage of dilution.

Drying @25°C

Overspraying (according to dilution) 30 mn Drying time for these stains depends on the type of applica tion and no guidelines can be given.

Surface Preparation

The surface must be clean, dry and free from paint and vanish, all previously painted surface must be cleaned of the coating by sanding or physical abrasion.

Application Method

These stains can be applied by hand-held or on-line spray guns, with running spray guns, roller or by immersion. After spray application, the stains can be wiped off also with line running brushes. The amount of thinning depends on the color required, the type of application, the type of material to be stained (material, shape and size). The choice of thinners depends on the conditions of work, application, the time available and the need to limit the emission of VOS (volatile organic substances) into the air.

Subsequent Treatments

The Exterior Gold Stain can be varnished with any type of clear coating, clear PU and NC products. Polyster based paints can only be used after a sealant has been applied.

Note

/ L O OOE) K = //

There is a stain product chart that reassume all these stains described in the Price List of EVI Vernici. All the color of the range are represented. The coloration has been obtained applying on maple.

Packing

Available in 1ltr and 5ltr.

Storage

If the drum is tightly closed and well stored at 25°C, the product have 18 months of shelf-life.