

# 2K PRIMER (AUTO) HARDENER

Product code: PS1756H

## Description & Suggested Use

The product is a HARDENER.  
Suggested use: Chemical cure of Acrylic Primer (Auto).

Product can be kept up to 18 months from production date only if storing instructions are correctly followed.

## General Information

The Acrylic Primer (Auto) mixed with the hardener PS1756H shows medium pot life and speed of cure. After drying, the catalyst allows the Acrylic to obtain a hard film with good clarity and fair light fastness. Anyway, the catalyst does not prevent the Acrylic from yellowing upon ageing.

## Safety Precaution

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. MSDS is available on request for the safe handling of this product.

## Specification

Specific Gravity @ 20°C (kg/L)	: 0.98 ± 0.01
Solid Content (% by volume)	: 24 ± 1
NCO (%)	: 4 ± 1

## FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

## Storage & Shelf Life

Keep the cans tightly close in a well ventilated place. Temperature should be controlled and kept between 10 to 30°C. The product is moisture sensitive and reacts with atmospheric humidity, protect from moisture contamination.