



## **Technical Data Sheet**

# **ALL ACRYLIC EMULSION**

Product code:PW3401

## **Composition and Application Field**

**EVI All Acrylic Emulsion** is a premium grade high performance acrylic topcoat formulated from special latex with inert pigments. The product has good alkali resistance properties and it is extremely low toxicity and odour. EVI All Acrylic Emulsion has very good weather resistance, durability and can be an ideal choice for both protective and decorative finish. It has very low dirt pick up and flexibility extends through a wide range of temperature.

## Use

**Substrates:** Concrete, plaster, masonry, Brick work and timber **Area of Use:** Interiors/ Exteriors

## **Specification**

Finish : Smooth

**Colour**: White and desired colours as per EVI

shade card

Specific gravity  $: 1.34 \pm 0.02$ Solids (% by volume)  $: 44 \pm 1$ Diluent : Sweet WaterFlash Point : Not Applicable

Spread Rate

While the spread rate is directly dependant on the surface profile and also the type of undulations it has, over spray and also the equipment EVI All Acrylic Emulsion would cover app  $10 - 11 \, \text{m}^2$  /litre.

**Drying time (30° C)** : Set to touch: <2 hours

: Ready for Recoat: app 3 hours

**Recommended DFT** : 1 to 2 coats. App 40 – 50 mic per

coat

## **Surface Preparation**

A good surface preparation and following the method statement / recommended system procedure of EVI is an ideal recommendation for the application of EVI All Acrylic Emulsion.

#### For Plaster, Masonry & Concrete:

Achieve a good and clean surface by removing all contaminants and loose particles by cleaning & drying. A laitance free surface should be achieved by good sweep blast or a wire brush. Water washing under pressure is recommended. If fungus is present then a good coat of EVI fungicidal wash compound is to be applied and rinsed properly after thorough drying. In case of interiors it is advisable to clean with a damp cloth. Apply EVI All Acrylic Primer, allow drying and then follow it with one or two coats of EVI All Acrylic Emulsion

#### **Application Method**

Adequate ventilation is an ideal situation as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point. One can add 5 to 10% of sweet water for ease of application depending on the suitability of application.

- 1. **Brush:** It is an ideal recommendation especially to avoid runs and sags due to excess material.
- 2. **Roller:** Apply an even coat spreading uniformly taking care to avoid runs.

## Storage & Shelf Life

Under dry and cool condition, storage stability can be sound up to 18 months in original sealed containers.

#### **HANDLING**

**Disposal:** As per the guidance and legislations of the local Authority e.g. by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Flash Point: Not applicable

## **Safety Precaution**

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

MSDS is available on request for the safe handling of this product.

## **FIRST AID**

**Eyes:** In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

**Skin**: Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.

**Inhalation**: Remove to fresh air, loosen collar and keep patient rested. **Ingestion**: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

The above Data Sheet is based on our experience and extensive laboratory tests. We guarantee only the quality of the product in this Data Sheet. For safety measurements and details refer to the Safety Data Sheet. Evi reserves the right to modify the contents of the Data Sheet at any time and without prior notice as a system requirement in updating the product.